Technical data sheet

Service outlet with blanking cover and opening contour, GES R2

Item number: 7405086



Service outlet with blanking cover and opening contour for GES R2 floor socket for direct installation in the MT R2 installation socket.

For use in dry-cleaned floors for indoor use.





PA

Polyamide

R/I	aste	 1040
IVI	aste	 ala

Item number 7405086 Type GES R2B 7011 Description 1 Floor socket Description 2 Plastic Manufacturer OBO Dimension 140x140x40 Colour Iron grey; RAL 7011 Material Polyamide Smallest sales unit 1 Unit of quantity Piece Weight 8.15 kg Weight unit kg/100 pc.		
Description 1 Floor socket Description 2 Plastic Manufacturer OBO Dimension 140x140x40 Colour Iron grey; RAL 7011 Material Polyamide Smallest sales unit 1 Unit of quantity Piece Weight 8.15 kg	Item number	7405086
Description 2 Plastic Manufacturer OBO Dimension 140x140x40 Colour Iron grey; RAL 7011 Material Polyamide Smallest sales unit 1 Unit of quantity Piece Weight 8.15 kg	Туре	GES R2B 7011
Manufacturer OBO Dimension 140x140x40 Colour Iron grey; RAL 7011 Material Polyamide Smallest sales unit 1 Unit of quantity Piece Weight 8.15 kg	Description 1	Floor socket
Dimension 140x140x40 Colour Iron grey; RAL 7011 Material Polyamide Smallest sales unit 1 Unit of quantity Piece Weight 8.15 kg	Description 2	Plastic
Colour Iron grey; RAL 7011 Material Polyamide Smallest sales unit 1 Unit of quantity Piece Weight 8.15 kg	Manufacturer	OBO
Material Polyamide Smallest sales unit 1 Unit of quantity Piece Weight 8.15 kg	Dimension	140x140x40
Smallest sales unit 1 Unit of quantity Piece Weight 8.15 kg	Colour	Iron grey; RAL 7011
Unit of quantity Piece Weight 8.15 kg	Material	Polyamide
Weight 8.15 kg	Smallest sales unit	1
	Unit of quantity	Piece
Weight unit kg/100 pc.	Weight	8.15 kg
J	Weight unit	kg/100 pc.

Technical data sheet

Service outlet with blanking cover and opening contour, GES R2





Technical data

Version for	Round
Cable outlet version	No cable outlet
Floor covering protection frame	yes
Floor care	Dry
Suitable for raised floor installation	yes
Suitable for cavity floor installation	yes
Suitable for wet care	no
Suitable for underfloor ducts	no
With floor covering recess	no
Standard	EN 50085-2-2
Protection rating (IP) when unused	IP40
Protection rating IK code	IK10
Vertical load, small area	to 500 N
Approvals	VDE
Opening mechanism	Tool