

Technical data sheet

Underfloor duct, 2 pieces, 2-compartment, duct height
28 mm

Item number: 7400256



Underfloor duct (2 piece) for routing cables in screed-covered underfloor systems, according to EN 50085-2-2. Removable and continuously lockable trunking cover. With separating retainers in the trunking base. Maximum load-bearing capacity to 1.5 kN.

The profiled side walls offer a locking mechanism to lock the duct cover onto the duct base. The stiffening beads in the duct cover serve to create stability.



St

Steel

FS

Strip galvanized

Master data

Item number	7400256
Type	S2 19028-2
Description 1	Underfloor duct, 2-part
Description 2	2 compartments
Manufacturer	OBO
Dimension	2000x190x28
Material	Steel
Surface	Strip galvanized
Surface standard	DIN EN 10346
Smallest sales unit	2
Unit of quantity	Metre
Weight	296 kg
Weight unit	kg/100 m
CO2 Footprint (GWP) Cradle-to-Gate	6,6718 kg CO2e / 1 Meter


Technical data sheet

Underfloor duct, 2 pieces, 2-compartment, duct height
28 mm

Item number: 7400256



Dimensions



Length	2,000 mm
Width	190 mm
Height	28 mm
Dimension a	80 mm
Dimension b	110 mm
Dimension h	28 mm

Technical data

Number of fixed partitions	1
Number of compartments	2 St.
Mounting system fastening type	Floor
Floor plate	yes
Application area	Screed-covered
Decouplable	no
Trunking width, min.	190 mm
Duct height, min.	28 mm
Usable cross-section	4629 mm ²
Removable cover	yes
Cross-section, draw a	1923 mm ²
Cross-section, draw b	2706 mm ²
Vertical load, large area	to 1,500 N