## **Technical data sheet**

## FireBox T250 with plug-in seals, 1 fuse holder

**Item number: 7205756** 





Junction box with one fuse holder and soft plug-in seals. Sufficiently large wiring compartment through diagonally arranged connection unit with completely premounted, high-temperature-resistant ceramic terminals. Green-yellow labelled protective conductor terminal. Fastening on easily accessible external flaps. Approved for cable systems that maintain the electrical function according to DIN 4102 Part 12 with the classes E30, E60 and E90. Ceramic clamps have been tested according to DIN EN 60998-2-1:2004.

Including 2 x MMSplus P 6x35 screw ties.











Polypropylene

### Master data

Item number	7205756
Туре	T250ED 16AF
Description 1	Junction box
Description 2	for function maintenance
Manufacturer	OBO
Dimension	240x190x95
Colour	Pastel orange; RAL 2003
Material	Polypropylene
Smallest sales unit	1
Unit of quantity	Piece
Weight	104.854 kg
Weight unit	kg/100 pc.
CO Footprint (GWP) Cradle-to- Gate	3,5941 kg COe / 1 Piece

# **Technical data sheet**

# FireBox T250 with plug-in seals, 1 fuse holder



**Item number: 7205756** 

#### **Dimensions** Length Width 240 mm 190 mm 0000 Height 95 mm Dimension B 190 mm Dimension H 95 mm 240 mm Dimension L Dimension L1 250 mm 270 mm Dimension L2

#### **Technical data**

240 250 270

Expandable	no
Number of terminals	6
Type of housing penetration	Cuttable stepped membrane
Equipment	Terminal
Cover	Not transparent
Cover fastening	Screwed
Entry from rear	no
Entries	9 x M25
	7 x M32
Explosion-tested version	no
Shape	Rectangular
Maintain electrical functions	E 90
For Ex zone	Without
For Ex zone gas	Without
For Ex zone dust	Without
Halogen-free	yes
Clear internal dimensions	225x173x86 mm
With screening	no
with lid	yes
Nominal cross-section, min.	16 mm²
Nominal voltage	660 V
Sealable	no
Impact-resistant	no
Protection rating	IP66
Transparent lid	no
Weatherproof	no